DEPARTMENT OF THE NAVY

COMMANDER
HELICOPTER TACTICAL WING
U.S. PACIFIC FLEET
NAS NORTH ISLAND P.O. BOX 357096
SAN DIEGO, CALIFORNIA 92135-7096

COMHELTACW INGPACINST 11320.1C N45

AUG 26 S98

COMHELTACWINGPACINST INSTRUCTION 11320 iC

Subj: COMHELTACWINGPAC FIRE BILL

Ref: (a) COMNAVBASEINST 11320.1B

End: (1) Emergency Phone Number List

~Im~U!m~

- 1. ~ $T6\sim i15Tish$ Bui jTh52 (Wes $\sim o\sim fyF\sim \sim$ fighting procedures and assign responsibilities for execution per reference (a)
- 2. <u>Cancellation</u> <u>COMHELTACWINGPAC 11320.1B.</u>
- 3. <u>Discussion</u>. Building 252 was built without a sprinkler system installed, therefore, if ignited, a fire will spread quickly. Rapid identification and reporting of any and all fires is paramount. It is essential that staff personnel be well versed in every means of reporting fires and the use of available fire fighting gear.
- 4. A~t.±.~n
 - a. <u>Discovery of Fire</u>
 - (1) Any person discovering a fire shall:
- (a) Immediately activate any available fire alarm system and, if safe to do so, notify occupants in the building. All fires, including extinguished fires, shall be reported immediately to the Fire Department.

COMHELTACWINGPACINST 11320.iC

AUG26 98

- (b) From a safe location dial telephone extension 9-911 and say "I want to report a fire." STAY ON THE TELEPHONE, ~DOINQT "!~ANG 1N~IL~TOLD ~TO DQ ~ The person on th l~e~phone will ask for all the pertinent information such as bulldTfi4~" number, type of fire, etc. In all cases, give exact location of fire. Keep in mind, the operator you are speaking to is not located onboard NASNI and it is necessary to specify exactly where the fire is located (i.e., Building 252, West wing, NAS North Island; see enclosure (1) for guidance)
 - (2) Fire alarm box operations. To operate a fire alarm box, open the box and pull down on the lever. Direct the Fire Department to the fire when they arrive on scene.
 - (3) In all cases, notify the CDO at 556-5500, extension or HC -- and great at 200 310 after making the cases.

CDO-Response to the large to the contract of t

- (1) Not by rederal Fire Department 9 Si. 4 1 mos already called).
- (2) Ensure the word is passed to all hands to evacuate the building.
 - (3) Notify the Commodore (5-2993)
 - (4) Notify Chief Staff Officer (5-5334)
 - (5) Notify SAFETY Department (5-5333)
 - (6) Notify NASNI QOD (5-8123)
- (7) Take charge at the scene of the fire until relieved by Fire Department personnel.
- (8) Post personnel to direct Fire Department personnel to scene of the fire.

CANCH26T\$68VINGPACINST 11320.ic

-U.-E

- (9) Keep all fire lanes clear of vehicles.
- (10) Log all drills and actual fires..-
- (11) Specific actions required to secure classified material during emergency situations are outlined in reference (a) and should be afforded highest priority without compromising personnel safety. The concern for personnel safety is paramount.
- (12) Take muster of all personnel and report same to the senior member present and fire department upon their arrival.

THE HELTACWING Personnel Responsibilities - All Hands (I) Recommed the demonstrate area of the second strains and the second strains are seco

- (b) Ensure Emergency dispatcher is called at extension 9-911. Do not assume the fire alarm will summon the fire department.
- (c) If you have been trained in the proper use of portable fire extinguishers, attempt to control the fire with available equipment until the fire is extinguished, or until relieved by the Fire Department. DO NOT JEOPARDIZE YOUR OWN PERSONAL SAFETY.
- (d) If time permits, secure windows, safes, files, and doors.
- (e) EXIT the building when the alarm sounds. Two minutes is assigned as a goal for evacuation.
 - (f) Always egress through the nearest exit.

AUG I 6 198

(g) All hands muster at the primary muster site depicted in enclosure (2). There shall be only one muster aree~----However,---if-_the_muster area is in proximi.t.y.~.to Lhe~-fl~ or interferes with the ~ fighting ~ all personnel at alternate muster site, depicted in enclosure (2)

d. Organizational Responsibilities

- (1) All hands not involved in fighting the fire shall remain clear of the building and fire fighting equipment.
- (2) The senior person in each work center or office shall take muster; eport to the CDO or his national and the Fibe made.

 Lower evaluation of all non-essential personners and the ene. A compared three distinct he read that some edition is the senior of the energy of
- (3) The Wing Safety Representative shall proceed to the scene of the fire and assist the CDO.
- (4) Upon arrival of Fire Department personnel, the senior Fire Officer will assume command of all fire fighting operations.

e. Inspections and Drills

- (1) Department Heads shall ensure no fire hazards exist in their areas of responsibility.
- (2) Department Heads shall ensure their personnel know and understand the fire bill, are familiar with escape routes, and know the locations of alarms and fire extinguishers as outlined in enclosures (2) and (3)

COMHELTACWTNGPACINST 11320.iC AUG 26 1BS~

- (3) All spaces shall be inspected for possible hazards each day prior to securing. All windows will be closed, appliances secured, and-all possible fire hazards removed prior t&r&cking the 'spaces.
- (4) The Safety Department shall schedule and document annual fire drills for Building 252. Drills shall be coordinated with the Chief Staff Officer.
- (5) Additionally, fire drills shall be coordinated with the NASNI Fire Prevention Branch (extension 5-8473)
- (6) Staff Fire Warden shall perform a monthly fire safety inspection using enclosure (4). All inspections shall be documented by signing and dathina le-closure. (4) tings! It is noted to the reserving user. If any major disampancies at the extragressure gauge the extinguisher shall be taken to the extinguisher maintenance shop, buriding 191 (extension 5-0752):
- (7) All discrepancies noted on extinguishers shall be reported •to the Staff Fire Warden. The Safety Office, Code N45, shall be informed separately.

K-,
D. A. MAWH~NNEY

Distribution:
COMHELTACWINGPACINST 5216.1C (CH-1)
LIST I, II, III

COMHELTACWINGPACINST 11320. iC AUG 6 1998

EMERGENCY PHONE NUMBERS

 U.
 ?~~4~TJLANCE
 9-911

 FIRE
 9—911

 POLICE
 9-911

 NAS OOD
 5-8123

CHTWP CDO 556—5500 extension 8781

I <u>NG</u>— <u>~</u>


YOUR PHONE NO._____

TYPE EMERGENCY: FIRE, ACCIDENT, INJURY, ETC

COMHELTACWINGPACINST 11320. iC

AUG 2 6 1998

COMHELTACWINGPAC BUILDING 252 LOWER DECK FIRE ESCAPE ROUTES



End (2)

FIRE BILL

~UILUIN~i NO;_~~-

IN CASE OF FIRE

- 1. USE NEAREST FIRE ALARM BOX OR TELEPHONE EXT. ___
 - ~i~iIme localism of the nearest alarm hex aind the nearest telepheas h your area. Wheitislug tiloplone, RIPORT UILOINE NUMBEt.
 - ~1irrl~II~iecFFfrs hpartme.t to the scene of fire.
- 2. SPREAD THE ALARM—PASS THE WORD.

 AU personnel except fire parties clear the area.
- 3. IF TIME PE.RM1TS~ CO~. AND WINDOWS TO CONFINE THE ~RE AND PREVENT L)~AF 1-S. UC NOT ENDANGER YOURSELF O~OTHERS IN THIS EFFORT.
- 4. USE PROPER EQUIPMENT AT HAND
 TO EXTINGUISH THE FIRE, PENDING
 ARRIVAL OF THE FIRE D~'ARTMENT.

NAVFAC 3-11320/9(4-67) * U.S.GPO: 1989-0-606-758 Supe, sedes NA VOOCKS 2079

S/N 0105-LF-001-6001

MONTHLY FIRE INSPECTION CHECKLIST

i-ri

Check pressure gauge for proper pressure (as applicable);

indicator should be within area identified as charged.

- Check that safety pin and seal are in place.
- Check condition of nozzle/hose for breaks or cracking. 3.
- 4. Check condition of extinguisher body for dents, rusting, etc.
- Check hydrostatic date stamped on cylinder. 5. If over five

~~Y~tIv~ne - S. tion - cies, sign and date

B~E~FTLLED 1N ON TAG:

- Type of extinguisher: i.e., Pressurized water, CO. 1.
- 2. Building number: 252 west.
- 3. Location of extinguisher: i.e., MTIP office.
- Month and year. 4. Date:
- Sign your name or initials. 5. Inspector:
- If any discrepancy is found, take extinguisher to fire building 791, and exchange for another. extinguisher maintenance,

COI~~T~?JINGPACINST 11320.iC

EXIT LIGHTS

1. Check for material condition.

2Yt~eck for- ~

of the "Press to Test" button.

EXITS

1. Ensure all required means of egress are continuous and unobstructed from any point in the building to a public way.

